



Quality Speaks Itself...

**PERFORMANCE CHART 3" REGULAR PUMPSET**

Group	Bowl & Impeller	Rotor	Version	Volt	Outer Diameter	Suitable for
Radial Flow	Modified PPO Noryl	EC Grade Copper	Single Phase	220 Volt 50Hz	Motor -74mm Pump -73mm	80 mm & above Dia. Borewell

Max. Head Per Stage 4.25 mtr.(14feet) ● Duty Point Head 3 mtr. ● Outlet (NRV) - 25mm (1")

(C-1)	DISCHARGE IN L.P.M.			8	15	18	22	28	33	44
	Model	H.P.	STG	Total Head in Meters						
	A13 - 10510	0.5	10	38	35	33	30	25	20	10
A13 - 107515	0.75	15	56	52.5	49	45	38	30	15	
A13 - 1120	1	20	68	63	59	54	45	36	18	
A13 - 11525	1.5	25	94	87.5	81	75	63	50	25	

Max. Head Per Stage 4.25 mtr.(14feet) ● Duty Point Head 3 mtr. ● Outlet (NRV) - 25mm (1")

(C-2)	DISCHARGE IN L.P.M.			20	30	33	40	45	55	65
	Model	H.P.	STG	Total Head in Meters						
	A13 - 207512	0.75	12	45	42	39	36	30	24	12
A13 - 207518	1	18	68	63	59	54	45	36	18	
A13 - 21520	1.5	20	75	70	65	60	50	40	20	

Max. Head Per Stage 4.25 mtr.(14feet) ● Duty Point Head 3 mtr. ● Outlet (NRV) - 32mm (1.25")

(C-4)	DISCHARGE IN L.P.M.			0	20	40	45	50	60	75
	Model	H.P.	STG	Total Head in Meters						
	A13 - 4058	0.5	8	36	32	26	24	20	16	8
A13 - 407510	0.75	10	45	40	33	30	25	20	10	
A13 - 4115	1	15	68	60	49	45	38	30	15	
A13 - 41518	1.5	18	81	72	59	54	45	36	18	

Max. Head Per Stage 4.25 mtr.(14feet) ● Duty Point Head 3 mtr. ● Outlet (NRV) - 32mm (1.25")

(C-7)	DISCHARGE IN L.P.M.			10	25	45	50	60	70	85
	Model	H.P.	STG	Total Head in Meters						
	A13 - 7055	0.5	5	23	20	16	15	13	10	5
A13 - 70758	0.75	8	45	40	33	30	25	20	10	
A13 - 7112	1	12	54	48	39	36	30	24	12	
A13 - 71515	1.5	15	68	60	49	45	38	30	15	



**Ajanta Industries**

Kishan Gate, B/h. Sahyog Complex, Plot No. G-413, G.I.D.C. Metoda, Dist. Rajkot. (Gujarat), India.

☎ 02827-287460, 287461

✉ info@ajantaindustries.co.in

🌐 www.ajantaindustries.co.in